



Greenshine New Energy
 GS-LED-L30 30W 6500K
 24 PCS CREE XTE LAMP 6500K 30W
 24 PCS CREE XTE LAMP 6500K 30W

Horizontal Footcandles
 Scale: 1 Inch = 20 Ft.
 Light Loss Factor = 0.90
 Lumens Per Lamp = N.A. (absolute photometry)
 Luminaire Lumens = 2531
 Mounting Height = 18.00 Ft
 Maximum Calculated Value = 1.11 Fc
 Arrangement: Single
 Arm Length = 3 Ft

PHOTOMETRIC FILENAME : IES_GREENSHINE_GS-LED-L30-30W 6500K TYPEIIM.IES

DESCRIPTIVE INFORMATION (From Photometric File)

Greenshine New Energy
GS-LED-L30 30W 6500K
24 PCS CREE XTE LAMP 6500K 30W
24 PCS CREE XTE LAMP 6500K 30W

TEMPLATE SPECIFICATION

Horizontal Footcandles
Scale: 1 Inch = 20 Ft.
Light Loss Factor = 0.90
Lumens Per Lamp = N.A. (absolute photometry)
Luminaire Lumens = 2531
Mounting Height = 18.00 Ft
Maximum Calculated Value = 1.11 Fc
Arrangement: Single
Arm Length = 3 Ft

LUMINAIRE LAYOUT INFORMATION

<u>#</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Orient</u>	<u>Tilt</u>	<u>Roll</u>	<u>Spin</u>	<u>Tilt Correction</u>
1	3.00	0.00	18.00	0.00	0.00	0.00	0.00	1.00